

White PVC 120 Chevron Top CTII

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

Application: Conveyorbelt open Chevron profile provides improved gripping in incline food handling applications. The FDA/USDA compliant POR compound is easy to clean and offers good resistance to animal fats, vegetable and mineral oils. The all-polyester, single-ply interwoven carcass offers low stretch, excellent fastener retention and good tear resistance, all at an economical price.



Technical Data

	Imperial
Working Tension	1 2 0 P IW
Number Of Plies	1
Fabric Type	S pun P oly
Top Surface	Chevron
Bottom Surface	F riction
Overall Gauge	0 .2 5 0 in.
Weight (Per Inch of Width)	0 .9 3 lbs /s q.ft.
Bottom Coefficient	0 .3 0 (approx.)
Minimum Rec. Pulley Diameters	2 .0 in.
Elongation At Rated Tension	< 2%
Working Temperature	2 0 to 1 8 0 F

Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Clipper *	Alligator *	Staple *
No	Yes	No	Yes	1 or UX1	15	125

* Fastener manufacturer should be consulted to review belt and application information.

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.