



A Division of R&P Inc.

White PVC 200

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

Application: This FDA/USDA compliant belt is a high performance, economical alternative to lightweight rubber belts in nut and seed sorting, meat and poultry, vegetable and fruit processing, or any other industry requiring a highly oil resistant conveyor belt. High-quality RMV compound is easy to clean, more stain resistant than conventional belts and provides excellent oil and chemical resistance. Superior fabrication qualities make this premium belt a great choice for a wide variety of applications.

Technical Data

| | Imperial |
|-------------------------------|----------------|
| Working Tension | 200 P IW |
| Number Of Plies | 1 |
| Fabric Type | Spun Poly |
| Top Surface | Smooth |
| Bottom Surface | Friction |
| Overall Gauge | 5/32" |
| Weight (Per Inch of Width) | .076 |
| Bottom Coefficient | 0.30 (approx.) |
| Minimum Rec. Pulley Diameters | 2 .0 in. |
| Elongation At Rated Tension | < 2% |
| Working Temperature | 2 0 to 1 8 0 F |

Splicing Methods

| FOF | Finger | Bias Stepped | Skived Bias | Clipper * | Alligator * | Staple * |
|-----|--------|--------------|-------------|-----------|-------------|----------|
| No | Yes | No | Yes | #3 | 7 | 125 |

* Fastener manufacturer should be consulted to review belt and application information.

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.