

White RMV 150

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

Application: This FDA/USDA compliant belt is a high performance, economical alternative to lightweight rubber belts in nut and seed sorting, meat and poultry, vegetable and fruit processing, or any other industry requiring a highly oil resistant conveyor belt. High-quality RMV compound is easy to clean, more stain resistant than conventional belts and provides excellent oil and chemical resistance. Superior fabrication qualities make this premium belt a great choice for a wide variety of applications.

Technical Data

	Imperial	Metric
Working Tension	150 PIW	26 KN/M
Number Of Plies	3	3
Fabric Type	Spun Poly	Spun Poly
Top Surface	Smooth	Smooth
Bottom Surface	Friction	Friction
Overall Gauge (Approximate)	0.135 in.	3.4 mm
Weight (Approximate)	0.85 lbs /sq.ft.	4.1 kg/sq.m.
Bottom Coefficient Of Friction	0.30 (approx.)	0.30 (approx.)
Minimum Rec. Pulley Diameters	2.5 in.	64 mm
Elongation At Rated Tension	< 2%	< 2%
Working Temperature	20 to 180 F	-7 to 82 C

Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Clipper *	Alligator *	Staple *
Yes	Yes	Yes	Yes	1 or UX1	7	125

* Fastener manufacturer should be consulted to review belt and application information.

Compliance (Government Regulations)

FDA/USDA	OSHA	MSHA	CSA	FRAS	NCB
	<300 Megohms	CFR 18.65	M422-87	1334.12	158:1989
Yes	No	No	No	No	No

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.