



A Division of R&P Inc.

## Black 150 Grade II

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

---

**Application:** Conveyorbelt's Heavy Duty Black Grade II belts are different from other belt manufacturers' "economical" belt lines. These belts will stretch less than 2% at full working tension and meet the Rubber Manufacturers Association's rating for Grade 2 rubber compounds. In addition, our belts have full skims between plies and excellent fastener retention safety factors of 8 to 1.

### Technical Data

	<b>Imperial</b>
<b>Working Tension</b>	150
<b>Number Of Plies</b>	2
<b>Fabric Type</b>	Poly/Nylon
<b>Top Surface</b>	1/32"
<b>Bottom Surface</b>	Bare
<b>Overall Gauge</b>	5/32"
<b>Weight (Per Inch of Width)</b>	.070
<b>Minimum Rec. Pulley Diameters</b>	4"
<b>Working Temperature</b>	-12/180 F

### Splicing Methods

<b>FOF</b>	<b>Finger</b>	<b>Bias Stepped</b>	<b>Clipper *</b>	<b>Alligator *</b>	<b>Staple *</b>
NO	NO	NO	2	15	125

\* Fastener manufacturer should be consulted to review belt and application information.

---

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.