



A Division of R&P Inc.

Black 220 RMA Grade II

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

Application: Conveyorbelt's Heavy Duty Black Grade II belts are different from other belt manufacturers' "economical" belt lines. These belts will stretch less than 2% at full working tension and meet the Rubber Manufacturers Association's rating for Grade 2 rubber compounds. In addition, our belts have full skims between plies and excellent fastener retention safety factors of 8 to 1.

Our Heavy Duty belt is designed for general purpose applications where material size is **4" or less, material drop is 3' or less and the idler toughing angle is 35 degrees or less.**

Technical Data

	Imperial
Working Tension	220
Number Of Plies	2
Fabric Type	Poly/Nylon
Top Surface	1/8"
Bottom Surface	Bare
Overall Gauge	15/64"
Weight (Per Inch of Width)	NA
Minimum Rec. Pulley Diameters	10"
Working Temperature	-12/180 F

Splicing Methods

FOF	Finger	Bias Stepped	Clipper *	Alligator *	Staple *
NO	NO	YES	4	25	187

* Fastener manufacturer should be consulted to review belt and application information.

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.