



A Division of R&P Inc.

## Black 275 RMA Grade II

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

---

**Application:** Conveyorbelt's Heavy Duty Black Grade II belts are different from other belt manufacturers' "economical" belt lines. These belts will stretch less than 2% at full working tension and meet the Rubber Manufacturers Association's rating for Grade 2 rubber compounds. In addition, our belts have full skims between plies and exhibit fastener retention safety factors of 8 to 1.

Our Heavy Duty belt is designed for general purpose applications where material size is 4" or less, material drop is 3' or less and the idler toughing angle is 35 degrees or less.

### Technical Data

	Imperial
Working Tension	275
Number Of Plies	3
Fabric Type	Poly/Nylon
Top Surface	1/16"
Bottom Surface	Bare
Overall Gauge	1/4"
Weight (Per Inch of Width)	.095
Minimum Rec. Pulley Diameters	12"
Working Temperature	-12/180 F

### Splicing Methods

Bias Stepped	Plate	Hinged	Staple	Rivet
YES	NO	375	187	R2

\* Fastener manufacturer should be consulted to review belt and application information.

---

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.