



A Division of R&P Inc.

## Black 220 MOR

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

---

**Application:** “MOR” – An economical and static conductive moderately oil resistant cover designed to withstand attack in moderately oily environments, such as wood chips, oil treated coal, and whole grains like corn and soybeans. Other applications include waste disposal, sewage and sludge.

### Technical Data

	<b>Imperial</b>
<b>Working Tension</b>	220
<b>Number Of Plies</b>	2
<b>Fabric Type</b>	Poly/Nylon
<b>Top Surface</b>	1/8”
<b>Bottom Surface</b>	1/16”
<b>Overall Gauge</b>	5/16”
<b>Weight (Per Inch of Width)</b>	.176
<b>Minimum Rec. Pulley Diameters</b>	10”
<b>Working Temperature</b>	-30/200 F

### Splicing Methods

<b>Vulcanized</b>	<b>Plate</b>	<b>Hinged</b>	<b>Hinged</b>
Bias	140	375	R5/187

\* Fastener manufacturer should be consulted to review belt and application information.

---

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.