

Black 220 MOR V-Cleat

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

Application:

FREE-FLOWING MATERIALS: V-Cleat belting is designed to handle the aggressive transfer and elevation of materials like coal, potash, stone, gravel, bark and wood chips. A chevron-top design locks free-flowing materials to the belt surface when the incline exceeds the capabilities of standard smooth belting. This prevents "slip-back" and the costly production losses that go with it.

CLEATS - The chevron cleats are an integral part of the original manufactured belt. Cleats are a full 1/4" high, with straight sides and a 3/8" base. With a 6" span, the chevrons repeat continuously across the width of the belt, overlapping from row to row to maintain a smooth running surface on the return idlers. For wet applications, the belt can be reversed to allow water to drain off the cleats while the load moves up the incline. V-cleat belt is normally available in 2 and 3 ply carcass constructions can be manufactured with and carcass. Special widths include 36" through 72".

Technical Data

	Imperial
Working Tension	220
Number Of Plies	2
Fabric Type	Poly/Nylon
Top Surface	1/8"
Bottom Surface	1/16"
Overall Gauge	1/2"
Weight (Per Inch of Width)	.214
Minimum Rec. Pulley Diameters	10"
Working Temperature	-30/200 F

Splicing Methods

Vulcanized	Plate	Hinged	Rivet
Bias	140/190	375	R5

* Fastener manufacturer should be consulted to review belt and application information.

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.