

## Black PVC 120

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

**Application:** An industry standard for general conveying, the belt's diverse applications include recycling, package conveying, fruits and vegetables, baggage and virtually all processing industries. The all-polyester, single-ply interwoven carcass provides low stretch, excellent fastener retention and good tear resistance, all at an economical price. The durable PVC compound offers mineral oil resistance and good wear characteristics.

### Technical Data

	Imperial	Metric
<b>Working Tension</b>	1 2 0 P IW	2 1 K N/M
<b>Number Of Plies</b>	1	1
<b>Fabric Type</b>	S pun P oly	S pun P oly
<b>Top Surface</b>	S mooth	S mooth
<b>Bottom Surface</b>	Friction	Friction
<b>Overall Gauge</b>	0 .1 3 5 in.	3 .4 mm
<b>Weight</b>	0 .8 3 lbs /s q.ft.	4 .0 kg/s q.m.
<b>Bottom Coefficient</b>	0 .3 0 (approx.)	0 .3 0 (approx.)
<b>Minimum Rec. Pulley Diameters</b>	3.0 in.	51 mm
<b>Elongation At Rated Tension</b>	< 2%	< 2%
<b>Working Temperature</b>	2 0 to 1 8 0 F	-7 to 8 2 C

### Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Clipper *	Alligator *	Staple *
NO	YES	NO	YES	2	15	125

\* Fastener manufacturer should be consulted to review belt and application information.

### Compliance (Government Regulations)

FDA/USDA	OHSA	MSHA	CSA	FRAS	NCB
	<300 Megohms	CF R 1 8 .65	M4 2 2 -87	M4 2 2 -87	1 5 8 :1989
No	No	No	No	No	No

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.