

## Black PVC 120 Chevron Top CTII

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

**Application:** Conveyorbelt's open Chevron profile provides improved gripping in incline food handling applications.



The all-polyester, single-ply interwoven carcass offers low stretch, excellent fastener retention and good tear resistance, all at an economical price.

### Technical Data

	Imperial	Metric
<b>Working Tension</b>	1 2 0 P IW	2 1 K N/M
<b>Number Of Plies</b>	1	1
<b>Fabric Type</b>	S pun Poly	S pun Poly
<b>Top Surface</b>	Chevron	Chevron
<b>Bottom Surface</b>	Friction	Friction
<b>Overall Gauge</b>	0 .2 5 0 in.	6 .4 mm
<b>Weight</b>	0 .9 3 lbs /sq.ft.	.5 kg/s q.m.
<b>Bottom Coefficient</b>	.3 0 (approx.)	.3 0 (approx.)
<b>Minimum Rec. Pulley Diameters</b>	2 .0 in.	51 mm
<b>Elongation At Rated Tension</b>	< 2%	< 2%
<b>Working Temperature</b>	2 0 to 1 8 0 F	-7 to 8 2 C

### Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Clipper *	Alligator *	Staple *
No	Yes	No	Yes	1 or UX1	15	125

\* Fastener manufacturer should be consulted to review belt and application information.

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.