



A Division of R&P Inc.

Black PVC 200

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

Application: An industry standard for general conveying, the belt's diverse applications include recycling, package conveying, fruits and vegetables, baggage and virtually all processing industries. The all-polyester, single-ply interwoven carcass provides low stretch, excellent fastener retention and good tear resistance, all at an economical price. The durable PVC compound offers mineral oil resistance and good wear characteristics.

Technical Data

| | Imperial |
|--------------------------------------|---------------------|
| Working Tension | 200 P IW |
| Number Of Plies | 1 |
| Fabric Type | S pun P oly |
| Top Surface | S mooth |
| Bottom Surface | F riction |
| Overall Gauge | 0 .1 3 5 in. |
| Weight | 0 .8 3 lbs /s q.ft. |
| Bottom Coefficient | 0 .3 0 (approx.) |
| Minimum Rec. Pulley Diameters | 2 .0 in. |
| Elongation At Rated Tension | < 2% |
| Working Temperature | 2 0 to 1 8 0 F |

Splicing Methods

| FOF | Finger | Bias Stepped | Skived Bias | Clipper * | Alligator * | Staple * |
|-----|--------|--------------|-------------|-----------|-------------|----------|
| NO | YES | NO | Yes | 4 | 27 | 187 |

* Fastener manufacturer should be consulted to review belt and application information.

Compliance (Government Regulations)

| FDA/USDA | OHSA | MSHA | CSA | FRAS | NCB |
|----------|-----------------|--------------|------------|------------|-------------|
| | <300 Megohms | CF R 1 8 .65 | M4 2 2 -87 | M4 2 2 -87 | 1 5 8 :1989 |
| No | No | No | No | No | No |

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.