



A Division of R&P Inc.

Black PVC 450

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

Application: An industry standard for general conveying, the belt's diverse applications include recycling and conveying. This belt offers excellent service in grain elevator legs. The all-polyester, single-ply interwoven carcass provides low stretch, excellent fastener retention and good tear resistance, all at an economical price. The durable PVC compound offers mineral oil resistance and good wear characteristics.

Technical Data

	Imperial
Working Tension	450
Number Of Plies	1
Fabric Type	Poly/Nylon
Top Surface	Smooth
Bottom Surface	Friction
Overall Gauge	5/16"
Weight (Per Inch of Width)	.183
Minimum Rec. Pulley Diameters	12"
Working Temperature	20 to 180 F

Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Plate	Hinged	Rivet
NO	YES	NO	NO	190	550	R5

* Fastener manufacturer should be consulted to review belt and application information.

Compliance (Government Regulations)

FDA/USDA	OHSA	MSHA	CSA	FRAS	NCB
	<300 Megohms	CF R 18 .65	M4 2 2 -87	M4 2 2 -87	1 5 8 :1989
No	No	No	No	No	No

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.