

Black RMV 150

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

Application: Black RMV 150 offers moderate oil resistance with excellent slider abrasion. This belt is ideal for conveying fertilizers, grains, oily products, agricultural produce and animal feeds. Its excellent in nut and seed sorting and many other agricultural and harvest uses.

Technical Data

	Imperial
Working Tension	150
Number Of Plies	2 or 3
Fabric Type	Spun Poly
Top Surface	1/32"
Bottom Surface	Friction
Overall Gauge	5/32"
Weight (Per Inch of Width)	.090
Minimum Rec. Pulley Diameters	3"
Working Temperature	0 to 180 F

Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Clipper *	Alligator *	Staple *
YES	YES	YES	Yes	1 or UX1	7	125

* Fastener manufacturer should be consulted to review belt and application information.

Compliance (Government Regulations)

FDA/USDA	OHSA	MSHA	CSA	FRAS	NCB
	<300 Megohms	CF R 18.65	M4 2 2 -87	M4 2 2 -87	158 :1989
No	No	No	No	No	No

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.